

# Hopper transfer Trans-eXpress

**Trans-eXpress  
500**

**Ingenuity  
Efficiency  
Security**



**PERARD**



With the flows more and more impressive of the combine harvesters, a harvest site has quickly need of 3 or 4 tipping trailers.

For removal by truck, the harvest with some tipping trailers must be emptied on the floor and reload with a bucket (requires a concrete platform).

A contractor on a small farm is often limited by the ability of farmers to evacuate the harvest.

Thanks to the Trans-Express, **a simple tipping trailer will be emptied directly into a truck.**

The advantages of this system apply equally to cooperatives, contractors or farmers.

With this system, 2 simples tipping trailers of 12-ton let you fill a truck. **No more time lost on the road, and no more risk.** Positioned on one point, many farmers can use it to load some trucks.



Model behind tractor



- Road approval for 130km/h (road model)
- Double axles / overrun brake (road model)
- Drawbar inertia (road model)
- 4 propstands at work
- Fender / standard light (road model)

- Drain pipe Ø500 mm
- Automatic gear
- Gearbox in 1"3/4-Z6

- Removable mesh sieve
- Tipping by traps or hydraulic doors
- Inclined tank to avoid overflow
- Flank lateral impact-resistant (optional)
- BERSE version available for use with a arm

- Drain height 4m90
- Hydraulic folding

Driven by tractor (PTD) 80 hp (for a single trap on the trailer) to 130 hp (with automatic door), Trans Express 500 has a double liftable axle (transport). The axle in the lower position allows the emptying of a low-rise tipping trailer or a truck.



## Technical Data

Tank length (inside)  
Overall Width  
Height (screw closed)  
Unload height  
Tank capacity  
Diameter of screw  
Grating inside  
Shock protection  
Transmission  
Wheels  
Brakes  
Road approval

## T-E 500

3.80 m  
1.65 m  
2.10 m  
4.90 m  
3.8 m<sup>3</sup>  
Ø 500 mm  
Serie  
Option  
Gears / Chain  
195/50 R13C  
Inertia  
130 or 25 km/h



Avenue de l'Europe  
Z.I. de Baleycourt  
F-55100 VERDUN

Tél: +33.(0)3.29.73.73.73

Fax: +33.(0)3.29.73.73.74

www.perard.fr - contact@perard.fr

10/12 - DC 39bUk - Pictures and data not contractual. Carefully to the various options can reduce the volume and load capacity.

This brochure is designed for use worldwide. The availability of different options or rates shown in the photographs may vary by country.

ISO 9001

BUREAU VERITAS  
Certification

